## **WELL™ 2.0**







WELL<sup>TM</sup> 2.0 makes battery-operated uplighting even easier with tri-colored LEDs calibrated to ensure consistency among fixtures as well as the COLORado<sup>TM</sup> line. WELL<sup>TM</sup> 2.0 runs on a built-in 12-volt battery capable of running for over 12 consecutive hours. For control, standard DMX ports are available as well as a pre-installed Wireless Solution W-DMX receiver with a new fixed antenna for better reception. The unit's reflective casing helps it blend in any environment where discreet installation is key. The charging base has also been improved to provide easy charging in any orientation within the 6-unit road case.

## **Features**

- 3, 4, 5, 6, or 10-channel tri-color RGB LED wash light
- Operating modes

3-channel: RGB control 3-channel: HSV control 4-channel: RGB, dimmer

5-channel: RGB, dimmer, strobe

6-channel: RGB control of both sides of array

10-channel: RGB, ID addressing, dimmer, strobe, macro, auto/custom,

dimmer curve, auto speed

- RGB color mixing with or without DMX control
- Color temperature presets (3,200 ~10,000 K)
- Built-in automated programs via DMX
- Recall custom programs via DMX
- Five distinct dimming curves
- 3-pin DMX input and output connectors
- Wireless DMX receiver built in
- Fixed position antenna for added stability
- LED display with password protection
- Split LED array can be focused individually
- Heavy-duty charging plug
- 12-hour battery life
- Movable foot on base of fixture for added positioning
- Color calibration



At a glance

RGB color mixing with or without DMX control

- Fixed position antenna for added stability
- · LED display with password protection
- 12-hour battery life
- · Movable foot on base of fixture for added positioning

## **Specifications**

• DMX Connectors: 3-pin

• Light Source: 12 3 W (1,050 mA x 3) tri-color LEDs 50,000 hrs

• Beam Angle: 17°
• Field Angle: 32°
• Lux: 225 @ 5 m

• IP Rating: IP44

AC Voltage Range: 100~240 V, 50/60 Hz (auto-ranging)
 Power Consumption 96 W, 0.42 A (charging) @ 230 V, 50 Hz

Battery Power: 12 V, 24 AhWeight: 36.3 lbs (16.5 kg)

• Size: 7.8 x 7.8 x 14.1 in (198.5 x 198.5 x 358 mm)

• Approvals: CE

