



Single Reeve	BGV-D8 capacity (US Ton) (kg)			Load Chain (in) (mm)	Weight Without Chain (lbs) (kg)	Duty Rate (%)	Dimensions (in) (mm)			Operating voltage	Motor Power (kW)	Contactor Control	Direct Control						
	Speed at 60 Hz (ft/min) (m/min)	Double Reeves	Speed at 60 Hz (ft/min) (m/min)				A	B	C										
1/4 250	16 4.8	1/2 500	8 2.4	5/32 x 1/2 4x12	33 15	25	12 1/2 317	7 13/32 188	4 3/8 110	220V, 3ph, 60 Hz Other Voltages on Request	0,27	Contactor Control Contactor inside the hoist itself	Direct Control Contactors in the distribution / control box						
1/4 250	24 7.2	1/2 500	12 3.6		59.4 27		40	14 3/16 360	10 1/4 260					6 1/8 155	0,75				
1/4 250	48 14.4	1/2 500	24 7.2	6/32 x 19/32 5x15	59.4 27	40	14 3/16 360	10 1/4 260	6 1/8 155		0,75			0,5	Direct Control Contactors in the distribution / control box				
1/3 320	16 4.8	2/3 640	8 2.4	5/32 x 1/2 4x12	33 15	25	14 1/16 357	7 13/32 188	4 3/8 110		0,5								
1/2 500	40 12	1 1000	20 6	9/32 x 7/8 7x22	60 27	40	14 3/16 360	10 1/4 260	6 1/8 155		220V, 3ph, 60 Hz Other Voltages on Request			0,84	Contactor Control Contactor inside the hoist itself	Direct Control Contactors in the distribution / control box			
1 1000	16 4.8	2 2000	8 2.4				25										14 3/4 374	16 1/2 419	2,2
1 1000	20 6	2 2000	10 3				25										19 13/16 503	13 3/8 340	3,6
1 1000	40 12	2 2000	20 6				25										21 533	7 11/16 195	2,2
1.6 1600	20 6	3.2 3200	10 3	3/8 x 1 1/16 9x27	128 58	25	19 13/16 503	13 3/8 340	7 11/16 195					3,6			2,2	Not available	
1.6 1600	40 12	3.2 3200	20 6	7/16 x 1 7/32 11x31	163 74	25	21 533	7 11/16 195	3,6										
2.5 2500	16 4.8	5 5000	8 2.4	7/16 x 1 7/32 11x31	163 74	25	21 533	13 3/8 340	7 11/16 195	220V, 3ph, 60 Hz Other Voltages on Request		2,2	Contactor Control Contactor inside the hoist itself	Direct Control Contactors in the distribution / control box					
2.5 2500	32 9.6	5 5000	16 4.8														3,6		